





Elegance 2.0

Flexibility to handle a wide range of applications



Elegance 2.0

Top performance, outstanding reliability and excellent design

The Elegance 2.0 impresses with modern looks as well as robust and dependable technology. Decades of experience and cutting-edge development work are perfectly matched in this product line. It uses materials which unite low weight and high resistance.

Triplex plunger pumps are available for the high-pressure system, and KAISER vane pumps or positive displacement blowers for the vacuum system. The respective pumps are located between the driver's cab and the tank. The components are hydraulically or mechanically driven depending on power requirements. This is performed by means of the power take-off on the carrier vehicle or a separate intermediate gearbox.

Versatility and high operator comfort

The well-conceived modular system allows the configuration of a broad spectrum of vehicles, from the compact 2-axle vacuum vehicle to the top-of-the-range 4-axle combination vehicle. The option of side-mounted water tanks in polyethylene or stainless steel enables the tank layout to be optimally adapted to the needs of the individual customer.

Vehicle operation has been designed with a focus on simple handling. A wide range of additional options as well as different suction boom versions, various jetting hose reels or ADR / ATEX round off the Elegance series.



DESIGN AND FUNCTIONALITY



INTELLIGENT DESIGN
ISN'T JUST VISIBLE –
IT'S ALSO PALPABLE.
SUPERSTRUCTURE
AND CARRIER VEHICLE
FORM A PERFECTLY
COORDINATED WHOLE.





DETAILS AT A GLANCE

Sludge tank dewatering

Additional feed pump



Radio remote control





Approvals



Street washing bar

Drainage control

TECHNICAL SPECIFICATIONS AND EQUIPMENT

Tank capacity	2-Axle Truck (18 to)	3-Axle Truck (26 to)	4-Axle Truck (32 to)
Sludge tank capacity (I)	5500-7300	10000-11400	12750-15000
Water tank capacity (I)	2700-5300	3000-5600	3200-5500
Wheelbase (mm)	3690-4300	3100-4500	4300-5300

Operation and control

- > Control panel towards the rear of the vehicle
- > Radio remote control with all the relevant operating functions
- Memory function for performance parameters (option)

High-pressure water system

- > High-pressure pumps with flow rates of 68 l/min and 50 bar up to 410 l/min and 170 bar
- > Jetting hose reel at side with manual or hydraulic drive for HP hoses of ½" to ¾", with manual or forced winding
- > Jetting hose reel at rear with hydraulic drive for HP hoses of 3/4" to 11/4"; with hydraulically slewable or fixed mounting including forced winding
- > Jetting hose reel model KSA for the combination of HP jetting hose and suction hose
- > Winter protection for temperatures of -5° to -20° C

Vacuum system

- Rotary vane vacuum pumps with water cooling and air flow rates of 984 m³/h to 1700 m³/h
- Rotary piston vacuum pumps with air flow rates of 1550 m³/h to 3900 m³/h
- Rear suction hose reel hinged, suction hose reel on tank in simple construction or with hose boom, for suction hoses with a diameter of 80, 100, 120 or 150 mm
- Various hydraulic suction boom types in 4", 5", 6", as basic or extended version

Tank structure

- > Tank in carbon steel or stainless steel
- > Tank structure with individual tank layout
- > Tipping system for complete emptying of the tank

SUPERSTRUCTURE DESIGN AND OPTIONS

Modular superstructure design

The Elegance line offers different versions for the ideal combination of fresh water and sludge tank, while simultaneously ensuring optimal axle load distribution and maximum payload.



Fresh water in front section of the tank, with permanent separation from sludge tank



Fresh water in side-mounted water tanks in polyethylene or stainless steel



Combination of fresh water tanks at front and sides

High-pressure and vacuum pumps



Rotary piston or rotary plunger vacuum pumps



Triplex high-pressure pumps

Suction boom



Combined suction/jetting boom

Standard suction boom



Spiral suction boom



Suction hose reel



Telescopic suction boom



Telescopic suction boom 360°

Jetting hose reel



Slewable reel



Fixed reel

Accessories



Winter protection



Metre counter



KAISER MORO ELEGANCE, THE FIRST SEWER CLEANING VEHICLE WITH A CLEAR DESIGN LANGUAGE



KAISER

THE RIGHT KAISER PRODUCT FOR YOUR APPLICATION

RECYCLING **VEHICLES**

WATER TREATMENT **VEHICLES**

COMBINATION VEHICLES

JETTING AND VACUUM VEHICLES

DRY VACUUM VEHICLES

HYDROVACS

MOBILE WALKING EXCAVATOR

ROAD-RAIL EXCAVATOR

S22RR



AquaStar

Eco 3.0

EcoCycler

CityCycler CityCleaner

AquaStar WT

KolDry

Combi Eur-Mark

Tornado

MicroCombi

Elegance 2.0

AquaStar

BasicLine



Tornado

Elegance 2.0

Twister

Special vehicles



Cerberus

Hercules

CV-Series

Urban X

S12 Allroad

S10

S8 Allroad / S8

S2



The international focus on modern environmental technologies has led to the growing importance of efficient, high-performance vehicles for sewer cleaning and industrial disposal. The KAISER Group is the leading player in the world market.

KAISER AG

Vorarlbergerstrasse 220 9486 Schaanwald, Liechtenstein T +423 377 21 21 kaiserag@kaiser.li www.kaiser.li

MORO KAISER S.R.L. Via Pontebbana, 16

33080 Fiume Veneto (PN), Italy T +39 0434 951 211 infomoro@morokaiser.it www.morokaiser.it

KAISER PREMIER LLC

2550 E. Bijou Ave. Fort Morgan, CO 80701, USA T +1 970 542 1975 sales@kaiserpremier.com www.kaiserpremier.com

OY EUR-MARK AB

Jakobstadsvägen 39 66900 Nykarleby, Finland T +358 20 73 45 800 info@eurmark.fi www.kaiser-eurmark.fi

KAISER Fahrzeugtechnik GmbH

Gewerbestraße 4 6710 Nenzing, Austria T +43 5525 641 80 mail@kaiser-fahrzeugtechnik.at www.kaiser-fahrzeugtechnik.at

KAISER Eastern Europe s.r.o.

Priemyselná 604/5 922 02 Krakovany, Slovakia T +421 33 7353 500 kaiser@kaiser-ee.sk www.kaiser-ee.sk